

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 10243 (1993): 2, 4-D Ethyl Ester EC [FAD 1: Pesticides and Pesticides Residue Analysis]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



भारतीय मानक

2, 4-डी इथाईल एस्टर – विशिष्ट

(पहला पुनरीक्षण)

Indian Standard

2, 4-D ETHYL ESTER EC — SPECIFICATION

(*First Revision*)

UDC 632.954 : 661.725-11/-12

© BIS 1993

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

January 1993

Price Group 2

FOREWORD

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Pesticides Sectional Committee had been approved by the Food and Agriculture Division Council.

2, 4-D ethyl ester EC is used as a weedicide.

The material is generally manufactured to contain 38 percent (*m/m*) 2,4-D ethyl ester having 34 percent (*m/m*) of 2,4-D acid.

In the preparation of this standard, due consideration has been given to the provisions of the *Insecticides Act*, 1968 and the Rules framed thereunder. However, this standard is subject to the restrictions imposed under these, wherever applicable.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*).' The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

2, 4-D ETHYL ESTER EC — SPECIFICATION

(First Revision)

1 SCOPE

This standard prescribes the requirements and the methods of sampling and test for 2,4-D ethyl ester EC.

2 REFERENCES

The Indian Standards listed below are necessary adjuncts to this standard:

| IS No. | Title |
|------------------------|---|
| 1070 : 1992 | Reagent grade water (<i>third revision</i>) |
| 1448 [P : 20] : 1984 | Methods of test for petroleum and its products : [P : 20] Flash point by Abel apparatus (<i>first revision</i>) |
| 6940 : 1982 | Methods of test for pesticides and their formulations (<i>first revision</i>) |
| 7233 : 1991 | 2,4-D ethyl ester, technical (<i>second revision</i>) |
| 8190 (Part 2) : 1988 | Requirement for packing of pesticides: Part 2 Liquid pesticides (<i>second revision</i>) |
| 10627 : 1983 | Methods for sampling of pesticidal formulations |

3 REQUIREMENTS

3.1 Constituents

3.1.1 The material shall consist of 2,4-D ethyl ester, technical, together with suitable solvent(s), emulsifier(s) and other formulants(s).

3.1.2 2,4-D ethyl ester, technical employed in the formulation of this material shall conform to IS 7233 : 1991 .

3.2 Description

The material shall be clear liquid, free from sediment. Suspended matter shall be negligible. It shall readily form an emulsion on dilution with water, suitable for spray.

3.3 Identity Test

When determined by the method prescribed in Annex G of IS 7233 : 1991 the retention time

of the 2,4-D ethyl ester present in the sample shall be the same as that of reference standard 2,4-D.

3.4 Physical

The material shall comply with physical requirements specified in 3.4.1 to 3.4.4.

3.4.1 Cold Test

No turbidity or separation of solid and/or oily matter or both shall occur when the material is subjected to cold test at 10°C as prescribed in 13.1 of IS 6940 : 1982 or any other lower temperature as agreed to between the purchaser and the supplier.

3.4.2 Flash Point (Abel)

When determined by the method prescribed in IS 1448 (P : 20) : 1984, the flash point of the material shall be above 24.5°C.

3.4.3 Emulsion Stability

Any separation including creaming at the top and sedimentation at the bottom of 100 ml of emulsion prepared in standard hard water with 2.0 ml concentrate, shall not exceed 2.0 ml when tested by the method prescribed in 13.3 of IS 6940 : 1982.

3.4.4 Heat Stability

After treating in accordance with the method prescribed in 13.4 of IS 6940 : 1982, the material shall comply with the requirements specified in 3.2, 3.4.3 and 3.5.

NOTE — The material need not be put to heat treatment, if the product has crossed half of its shelf life, as ascertained from the date of manufacture and date of expiry declared on the container.

3.5 Chemical

The material shall comply with the chemical requirements specified in 3.5.1 and 3.5.2.

3.5.1 2,4-D Ethyl Ester Content

When determined by the method prescribed in Annex A, the observed 2,4-D ethyl ester content percent (*m/m*) of any of the samples shall not differ from the declared nominal

value by more than the percent tolerance limits indicated below:

| Nominal Value, Percent | Tolerance Limits, Percent | |
|------------------------|---------------------------|------------------------|
| Up to 9 | +10 - 5 | } of the nominal value |
| Above 9 and below 50 | ± 5 | |
| 50 and above | + 5 - 3 | |

3.5.2 Free 2,4-D

When tested by the method prescribed in Annex B of IS 7233 : 1991 free acidity (as 2,4-D acid) shall not be more than 4 percent by mass.

4 PACKING

The containers shall be packed according to the requirements given in IS 8190 (Part 2) : 1988.

5 MARKING

The containers shall bear legibly and indelibly the following information in addition to any other information required under the *Insecticides Act*, 1968 and Rules:

- Name of the material;
- Name of the manufacturer;
- Batch number;

- Date of manufacture and date of expiry;
- Net mass of contents;
- Nominal 2,4-D ethyl ester content, percent (*m/m*); and
- A cautionary notice worded as in the *Insecticides Act*, 1968 and Rules.

6 SAMPLING

When material in bulk quantity is offered for inspection, representative samples shall be drawn and tested for conformity as prescribed in IS 10627 : 1983 within 90 days of its manufacturing. When the material is offered for inspection after 90 days of its manufacturing, samples shall be drawn as prescribed in IS 10627 : 1983. However, the criteria for conformity shall be the limits of tolerances as applicable over the declared nominal value and given under 3.5.1 of this standard.

7 TESTS

7.1 Tests shall be carried out by the appropriate methods referred to in 3.3 to 3.5.2.

7.2 Quality of Reagents

Unless specified otherwise, pure chemicals and distilled water (*see* IS 1070 : 1992) shall be employed in tests.

NOTE — 'Pure chemicals' shall mean chemicals that do not contain impurities which affect the results of analysis.

ANNEX A

(Clause 3.5.1)

DETERMINATION OF 2, 4-D ETHYL ESTER CONTENT

A-1 GENERAL

Total extractable 2,4-D content, percent by mass shall be estimated by the method specified under A-3. Free 2,4-D content, percent by mass shall be estimated by the method specified in Annex B of IS 7233 : 1991. 2,4-D ethyl ester content shall be then calculated by multiplying the difference between the total extracted 2,4-D and free 2,4-D by the factor 249/221.

A-2 REAGENTS

A-2.1 Potassium Hydroxide — Pellets.

A-2.2 Isopropanol

A-2.3 Petroleum Ether

A-2.4 Phenolphthalein Indicator — 1 percent solution in 96 percent ethanol (*m/m*).

A-2.5 Hydrochloric Acid — 1 : 1 (*v/v*).

A-2.6 Ammonium Hydroxide — 1 : 1 (*v/v*).

A-2.7 Barium Chloride Solution — 0.1 percent aqueous solution (*m/v*).

A-2.8 Methyl Orange Indicator — 0.1 percent aqueous solution (*m/v*).

A-2.9 Diethyl Ether

A-2.10 Silver Nitrate Solution — 5 percent (*m/m*).

A-2.11 Ethanol — Neutral, alternatively methanol, neutral may be used.

A-2.12 Sodium Hydroxide Solution — 0.1 N.**A-2.13 Bromothymol Blue Indicator Solution**

0.04 percent solution in alcohol (*m/m*).

A-3 PROCEDURE

A-3.1 Weigh accurately an amount of the sample equivalent to about 1 g of 2,4-D into a round-bottom flask, add about 1.5 g of potassium hydroxide pellets, 80 ml isopropanol, 20 ml distilled water and 2-3 glass beads. Fit a reflux condenser and heat vigorously under reflux for about an hour.

A-3.2 Cool, filter the contents of the flask, wash the flask thoroughly with 10 ml portions of distilled water 6 to 7 times or until traces of alkali are removed when tested by phenolphthalein indicator solution. Filter and collect the filtrate into a 500-ml separatory funnel. Extract the contents of the separatory funnel with two 50 ml portions of petroleum ether to remove unsaponifiable oils. Carefully draw off the aqueous phase into a 500-ml beaker and evaporate it on a water bath, slowly and carefully, until the volume is reduced to about 50 ml.

A-3.3 Cool and transfer the solution into a 250-ml volumetric flask, wash the beaker 2 to 3 times with small portions of distilled water and transfer the washings also to the volumetric flask. Add a few drops of hydrochloric acid until the disappearance of alkalinity. Add ammonium hydroxide and make the solution alkaline and check with phenolphthalein indicator. Carefully add 3 ml of barium chloride and shake continuously to precipitate any fatty acid derived from the saponification. Dilute the solution to the mark with distilled water and allow to stand for about 5 minutes with occasional stirring.

A-3.4 Filter the contents of the volumetric flask into a 250-ml beaker. Take out with pipette 100 ml of filtrate into a 250-ml separatory funnel and using methyl orange indicator

acidify with hydrochloric acid. Extract the 2,4-D acid with three 25 ml portions of diethyl ether. After each extraction with ether, allow sufficient time for the layers to separate. Combine the three ether extracts and wash with successive portions of distilled water till free of chlorides (about 10-15 ml washings should not give any precipitate with silver nitrate). Transfer the contents of the separatory funnel into a 500-ml conical flask, wash the separatory funnel with 2 small portions of ether, collect the washings also into the conical flask. Add 80 ml ethanol, and titrate with standard sodium hydroxide solution using bromothymol blue indicator.

A-3.5 Carry out a blank determination with 75 ml ether and 80 ml ethanol.

A-4 CALCULATION**A-4.1 Total extractable**

$$\begin{array}{l} \text{2, 4-D content,} \\ \text{percent by mass} = \frac{(V_1 - V_2) \times N \times 2.5 \times 22.1}{M} \end{array}$$

where

V_1 = volume, in ml, of standard sodium hydroxide solution required for the test;

V_2 = volume, in ml, of standard sodium hydroxide solution required for the blank determination;

N = normality of standard sodium hydroxide solution; and

M = mass, in g, of sample taken for the test.

$$\text{A-4.2 2, 4-D ethyl ester content} = (A - B) \times \frac{249}{221}$$

where

A = Total extractable 2,4-D content (see A-4.1); and

B = Free 2,4-D content (see 3.5.2).

Standard Mark

The use of the Standard Mark is governed by the provisions of the *Bureau of Indian Standards Act, 1986* and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Revision of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also revised periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook' and 'Standards Monthly Additions'. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc : No FAD 1 (4002)

Amendments Issued Since Publication

| Amend No. | Date of Issue | Text Affected |
|-----------|---------------|---------------|
| | | |
| | | |
| | | |

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002
Telephones : 331 01 31, 331 13 75

Telegrams : Manaksanstha
(Common to all Offices)

Regional Offices :

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg
NEW DELHI 110002

Telephone

{ 331 01 31
{ 331 13 75

Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola
CALCUTTA 700054

{ 37 84 99, 37 85 61
{ 37 86 26, 37 86 62

Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036

{ 53 38 43, 53 16 40
{ 53 23 84

Southern : C. I. T. Campus, IV Cross Road, MADRAS 600113

{ 235 02 16, 235 04 42
{ 235 15 19, 235 23 15

Western : Manakalaya, E9 MIDC, Marol, Andheri (East)
BOMBAY 400093

{ 632 92 95, 632 78 58
{ 632 78 91, 632 78 92

Branches : AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE.
FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR.
LUCKNOW. PATNA. THIRUVANANTHAPURAM.

**AMENDMENT NO. 1 MAY 1994
TO
IS 10243 : 1993 2,4-D ETHYL ESTER EC —
SPECIFICATION**

(First Revision)

(Page 1, clause 3.4.4) — Delete.

(FAD 1)

Reprography Unit, BIS, New Delhi, India

AMENDMENT NO. 2 JANUARY 1998
TO
IS 10243 : 1993 2, 4-D ETHYL ESTER EC —
SPECIFICATION

(First Revision)

(Page 3, clause A-4.2) — Substitute the following for the existing matter:

'A-4.2 2, 4-D ethyl

$$\text{ester content} = A \times \frac{249}{221}$$

where

A = total extractable 2, 4-D content.'

(FAD 1)

Reprography Unit, BIS, New Delhi, India